



公差等级/General Tolerances(mm)	
0	>3
3	~6
6	~10
10	~18
±0.12	±0.18 ±0.22 ±0.26 ±0.31 ±0.37 ±0.57 ±0.80 ±0.93 ±1.05 ±1.15 ±1.60 ±2.20 ±2.50
~50	~80
~120	~180
~250	~315
~400	~500
~500	~>500
0.1/10	±Z

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	SCALE: 2:1	SHEET 1/1
<p><b>DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD</b></p> <p>NINGBO DEGSON ELECTRICAL CO., LTD</p> <p>NAME: ZEDGKM-5.08-XXP-1Y-1000A(H)</p> <p>DRAWING NO.: ZEDGKM-5.08-C36</p> <p>TYPE: CUSTOMER DRAWING</p>							
<p>MATERIAL: /</p> <p>SURFACE: /</p> <p>MAT NO.: /</p> <p>STATUS: /</p> <p>APPD: LanQH 2020.005.26</p> <p>CHKD: GongYh 2020.05.26</p> <p>DFT: FRZ 2015.11.16</p>							
<p>ITEM NAME OF PART MATERIAL NOTES</p> <p>1 Housing PA66 UL94V-0</p> <p>2 Cover PA66 UL94V-0</p> <p>3 Screw 1 Steel M3/Zn Plated</p> <p>4 Cage Copper alloy Ni Plated</p> <p>5 Clamp Copper alloy Sn Plated</p> <p>6 Screw 2 Steel M2.5/Zn Plated</p>							
<p>UL 标准/UL Standard: B 300/15 C 300/70 D 300/70</p> <p>额定电压/电涌/Rated Voltage(V)/Current(A) III/3 III/2 II/2</p> <p>IEC 标准/IEC Standard: III/3 III/2 II/2</p> <p>过压类别/Overvoltage Category/污染等级 III/3 III/2 II/2</p> <p>额定电压/电涌/Rated Voltage(V)/Current(A) / / 320/20 /</p> <p>额定脉冲电压(kV)/Rate Impulse Voltage(kV) / / 4 /</p> <p>额定扭矩/扭矩 Tightening(N·m) M3, 0.58</p> <p>导线范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG) 1.0~2.5/28~12</p> <p>间距/Pitch(mm)/线数范围/Poles 5.08/N=02~22P</p> <p>剥线长度/Stripping length(mm) 7~8</p> <p>使用温度范围/Operating temperature(°C) -40~+105</p> <p>符合RoHS要求/Conform to RoHS Yes</p>							