



公差表/General Tolerances(mm)		0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.43	±0.51	±0.57	±0.60	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2

MATERIAL: /  
SURFACE: /

MAT NO: /

STATUS: /

APPL:an CHH 2021.05.10

CHKD:Yu JZh 2021.05.10

DRAFT:Chen Zh 2021.01.25

DRAWING NO.: 10004319

TYPE: CUSTOMER DRAWING

NAME: 宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD

DG2216V-10.0-XXP-1Y-00A(H)

DRAFT:Chen Zh 2021.01.25

DATE: 2021.05.10

SIZE: A4

UL Standard:	B	C	D
UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/66	600/66	/
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	400/76	400/76	630/76
额定脉冲电压/电流/Rate Impulse Voltage(KV)	4	4	4
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~16(25mm <sup>2</sup> soil)/18~4		
剥线长度/Stripping length(mm)	18~20		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

REV	ECN	DESCRIPTION	DRAFT	DATE
11	20210086	1xAdd the UL lettering	Chen Zh	2021.05.10