



公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)		公差 (mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	>630	>800	>1000	>1250
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±3.15	±4.00	±5.00	±6.30

ITEM	NAME OF PART	MATERIAL	NOTES
6	Spring	Stainless steel	/
5	Clamp	Copper alloy	Sn Plated
4	Cover	PA66	UL94V-0
3	Housing3	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0

  

UL 标准 / UL Standard:	B	C	D
额定电压 / Rated Voltage(V) / Current(A)	300 / 15	/	/
EC 标准 / IEC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III / 3	III / 2	II / 2
额定电压 / 电流 / Rated Voltage(V) / Current(A)	320 / 20	/	/
额定脉冲电压 / 电流 / Rate Impulse Voltage(KV)	4	/	/
线径范围 (硬线和软线) / Wire Range(rigid and flexible)(mm <sup>2</sup> / AWG)	0.2~2.5 / 22~14		
间距 / Pitch(mm) / 线数范围 / Poles	5.0 / N=02~24P		
剥线长度 / Stripping length(mm)	7-8		
使用温度范围 / Operating temperature(°C)	-40~+105		
符合RoHS环保要求 / Conform to RoHS	Yes		
标准颜色编号 / Standard color number:	7534U		

MATERIAL:	/	SURFACE:	/
MAT NO.:	/		
STATUS:	/		
APPD:	LonCHH 2020.04.09		
CHKD:	GongYzh 2020.04.09		
DRFT:	LY 2020.01.09		
NAME:	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD		
DRAWING NO.:	10001827	REV	T0
TYPE:	CUSTOMER DRAWING	SCALE:	2:1 SHEET 1/1

管 发 中 心  
研 发 专 用  
2020.04.09  
(仅限内部使用, 对外无效)

REV	ECN	DESCRIPTION	DRFT	DATE