



未注公差/General tolerances (mm)													0.1/10	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400		>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)	24/6.3	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	/	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.5/4.43		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	20~10 / 0.5~4.6 (Sol)		
间距/Pitch(mm)/线数范围/Poles	8.0/01P		
剥线长度/Stripping length(mm)	9		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

7	LED lamp assembly	/	/
6	Screw	Steel	Zn plated
5	Cage	Steel	Zn plated
4	Clamp	Copper	Sn plated
3	Spring	Stainless steel	/
2	Body housing	PA66	UL94V-0
1	Fuse housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

		MATERIAL: /	SURFACE/COLOR: /		
		MAT NO./REV: /	MAT STATUS: /		
APPD: Peng M	2022.08.20	NAME			
CHKD: Gao WG	2022.08.20	DC4-HE-LD24-01P-1Y-00A (H)			
DRFT: Huang RJ	2022.08.20	DRAWING NO. /	TYPE	DRAWING STATUS	SCALE
		CUSTOMER DRAWING		/	1:1
				SHEET	1/1

REV	ECN	DESCRIPTION	DRFT	DATE
00	/	/	Huang RJ	2022.08.20

Transfer or duplication of this document as well as the utilization or communication of its content are prohibited unless authorized in writing by Degson. All rights reserved for patent. 未经授权，禁止复制或传播本文件内容。本文件内容仅供参考，使用时请仔细阅读。除专利等明确标注外，其他内容均不作为侵权的依据。