



公差表 (General Tolerances)(mm)		0.1/10
0	>3	±7
~ 3	~ 6	~ 3
~ 6	~ 10	~ 2
~ 10	~ 18	~ 1.5
~ 18	~ 30	~ 1
~ 30	~ 50	~ 0.7
~ 50	~ 80	~ 0.5
~ 80	~ 120	~ 0.4
~ 120	~ 180	~ 0.3
~ 180	~ 250	~ 0.25
~ 250	~ 315	~ 0.2
~ 315	~ 400	~ 0.15
~ 400	~ 500	~ 0.12
~ 500	>500	~ 0.1
±0.12	±0.18	±0.25
±0.22	±0.26	±0.31
±0.31	±0.37	±0.57
±0.80	±0.93	±1.05
±1.15	±1.60	±2.20
±2.50		

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Current carrier	Copper	Sn Plated

额定电流/Rated Current(A)	8
回距/Pitch(mm)/线数范围/Polies	3.5/N-02-03P
使用温度范围/Operating Temperature(°C)	-40~+105
符合RoHS环保要求/Conform to RoHS	Yes

DEGSON	MATERIAL: PA66	SURFACE/COLOR:
APPD: 2023.08.14	MAT NO./REV: -	/00
CHKD: 2023.08.11	MAT STATUS: 批	

APPD: 2023.08.14	NAME	DC031-3.5-XXP-1Y-00Z(H)
CHKD: 2023.08.11	DRAWING NO.	200032279
DRAFT: 2023.08.11	TYPE	CUSTOMER DRAWING
DATE: 2023.08.11	DRAWING STATUS	E2
DRAFT: 2023.08.11	SCALE	5:1
DATE: 2023.08.11	SHEET	1/2

1 2 3 4 5 6

D

C

B

A